

1080Q Double-Sided Infinite Beam

Model: **BMS-1080Q** · Moving Head Beam · Rev. 2026-10

OPTICAL SYSTEM

Light Source	10 × 80W RGBW LEDs 360 × 3W Warm White LEDs, 360 × 3W White LEDs (Peripheral Auxiliary)
Colour	Red, Green, Blue, White
Auxiliary Colour	Warm White, White
Optical Features	Infinite rotation + beam + strobe + auxiliary light

MOVEMENT

Tilt	360°(Auto-correction for misalignment)
------	--

CONTROL

DMX Channels	31/44/76 channels
--------------	-------------------

POWER

Power Input	AC100–240V, 50/60Hz
Power Consumption	750W
Power Connection	Power connector input/output

CONSTRUCTION

Housing Material	Iron + Plastic
Housing Colour	Black
IP Rating	IP20
Operating Temperature	0 °C to 40 °C



KEY FEATURES

- High-output professional light engine
- Precision optics for bright, uniform output
- Smooth dimming and multi-mode strobe effects
- DMX512 / RDM control with LCD display
- Rugged black housing optimized for touring

TYPICAL APPLICATIONS

Concerts · Clubs · Theatre productions · Festivals · Live events

Specifications are subject to change without prior notice. Values above are taken from the current production datasheet for BMS-1080Q. Photometric (IES/LDT) files, packaging dimensions and OEM/ODM options are available on request.