

Lifting Beam Strobe

Model: **BMS-LIFTSTROBE** · Moving Head Beam · Rev. 2026-10

CONTROL

DMX Channels	41/101 channels
--------------	-----------------

POWER

Power Input	AC90-240V, 50/60Hz
Power Consumption	800W
Power Connection	Power connector input/output

CONSTRUCTION

Housing Material	Aluminum + Plastic
Housing Colour	Black
IP Rating	IP20
Operating Temperature	5 °C to 45 °C
Cooling	Fans

LIFTING HOST

Lifting Stroke	6-10 Meters
Maximum Load	15 kg
Lifting Host Power	50W
Lifting Host Net Weight	15 kg
Lifting Host Gross Weight	16 kg

BEAM EXPOSURE

Beam Exposure Type	20 × 40W OSRAM 4-in-1 LEDs (Double-sided Beam) 240 5W 7575 White LEDs, 480 0.5W RGB LEDs (Strobe)
Beam Exposure Angle	3°
Outlet Aperture	70mm
Length	102cm
Beam Exposure Dimmer	0-100% linear dimming
Beam Exposure Strobe	Horse-running, flash effect
Beam Exposure Pixel	Single LED can be controlled individually
Beam Exposure Power	700W
Beam Exposure Net Weight	8 kg
Beam Exposure Gross Weight	9 kg



KEY FEATURES

- High-output professional light engine
- Precision optics for bright, uniform output
- Smooth dimming and multi-mode strobe effects
- DMX512 / RDM control with LCD display
- Rugged black housing optimized for touring

TYPICAL APPLICATIONS

Large concerts · Nightclubs · TV shows · Exhibitions · Stage productions

Specifications are subject to change without prior notice. Values above are taken from the current production datasheet for BMS-LIFTSTROBE. Photometric (IES/LDT) files, packaging dimensions and OEM/ODM options are available on request.